

TECHNICAL SPECIFICATIONS – MultiFlash LR Q+

WEIGHT / DIMENSIONS

Length39.3" (998mm)
 Width 5" (125mm)
 Height (w/yoke) 6.9" (175mm)
 Weight24.3 lb.(11 kg)

POWER

Operating Voltage00-240VAC 50/60Hz
 Fuse.....12A 250V slow-blow (5x20mm)
 Power consumption.....1400W

LIGHT SOURCE

LEDs.....108 RGBW Cree LEDs divided into 12 pixels
 ColorRGBW
 Beam spread36°
 Intensity control..... 16bit or 8bit
 Refresh rate 1200Hz

AVERAGE COLOR WAVELENGTH

Red625 nm
 Green530 nm
 Blue460 nm
 White>5700K
 Refresh rate 1200Hz

THERMAL

Max. ambient temperature.....+104°F (+40 °C)
 Min. ambient temperature.....-4 °F (-20 °C)
 Coolingair cooled – fan

CONTROL / PROGRAMMING

DMX inputlocking 5-pin XLR male socket
 DMX output locking 5-pin XLR female socket
 DMX pin config. pin 1 shield, pin 2 (-), pin 3 (+), pin 4 n/a, pin 5 n/a
 ControlRDM, DMX-512, Demo, Manual Mode
 DMX Channels – Basic Mode..... 3,4,6,7,8
 DMX Channels - Advanced Mode..... 10,12,13,16,19,20,24,25,32,43,56
 Power ConnectorInput: PowerCon 20A

