

TECHNICAL SPECIFICATIONS – MultiFlash M3

WEIGHT / DIMENSIONS

Length	13.0" (329mm)
Width	5.25" (133mm)
Height (w/yoke)	9.2" (233mm)
Weight	10.6 lb. (4.8 kg)

POWER

Operating Voltage	100-240VAC 50/60Hz
Fuse.....	12A 250V slow-blow (5x20mm)
Power Consumption	400W

LIGHT SOURCE

LEDs.....	32 10W RBGW Cree LEDs divided into 4 segments
Color	RGBW
Beam spread	36°

THERMAL

Max. ambient temperature.....	+104°F (+40 °C)
Min. ambient temperature.....	-4 °F (-20 °C)
Cooling	air cooled – fan

CONTROL / PROGRAMMING

DMX input	locking 5-pin XLR male socket
DMX output	locking 5-pin XLR female socket
DMX pin config.	pin 1 shield, pin 2 (-), pin 3 (+), pin 4 n/a, pin 5 n/a
Control	RDM, DMX-512, Demo, Manual mode
Demo, Manual mode	
DMX Channels – Basic Mode.....	3,4,6,7,8
DMX Channels - Advanced Mode.....	10,12,13,16,19,20,24,25,32,43,56
Power Connector	Input: PowerCon 20A

